

## Non Flammable Contact Cleaner

Product Code: CCL

### PRODUCT DESCRIPTION

**CCL** is a very fast evaporating solvent cleaner developed for use on live electrical equipment to clean switches and contacts. It is a unique product as it is 100% Ozone Friendly, non- flammable and evaporates quickly, leaving no residue. The low surface tension means that it has exceptional penetrating power.

### PRODUCT USE

For use as a cleaner for electrical contacts and switches to ensure low contact resistance. Plastics compatible and non flammable, it can be used on live equipment where flammable solvents are prohibited.

### FEATURES

- \* Loosens and removes accumulated deposits of dirt grease and oxides.
- \* Low toxicity
- \* Non-flammable.
- \* Fast drying
- \* Safe with plastics and rubbers
- \* 100% Ozone Friendly

### TYPICAL PROPERTIES

Specific Gravity @ 20°C:	1.49
Flash Point:	None
Relative Evaporation Rate:	> 1 (Butyl Acetate=1)
Residue on Evaporation:	None
Viscosity	0.63 cps
Vapour Pressure	39.7 KPa
Boiling Point	43°C
Solubility	Sparingly soluble in water.

TECHNICAL  
DATA  
SHEET



### **Copyright Electrolube 2003**

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.



## Non Flammable Contact Cleaner – Page 2

### DIRECTIONS FOR USE

Spray directly onto the contacts and switches to be cleaned. The power of the jet will clean the contacts, leaving no residues. Buds or cloths may also be used if desired.

### PACKAGING

200ml Aerosol with brush

### ORDER CODE

CCL200

### TECHNICAL DATA SHEET



### Copyright Electrolube 2003

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

