

Graffiti Remover Gel

Product Code: GRG400

PRODUCT DESCRIPTION

Graffiti Remover Gel has been specially formulated for the quick and efficient removal of felt tip pen, ball point pen ink, most paints, crayon, lipstick and stencilling ink. Removes from many different types of surface including glass and plastic, painted metalwork, brickwork and wooden surfaces

PRODUCT USE

For the removal of graffiti from all types of surface. Product contains nonionic surfactants in a mixture of non-aromatic solvents. The product is propelled by liquefied petroleum gas and should be kept away from naked flames and heated surfaces.

Shake can well before use. Spray aerosol onto surface from 10 – 30 cm, depending on width of spray required. Allow to be absorbed for 1 – 5 minutes (depending on age and stubbornness of stains). Remove softened ink or paint with a cloth or brush.

Repeat procedure if required.

FEATURES

- * High viscosity gelled product – clings to vertical surfaces
- * Low volatility - longer contact time
- * Removes graffiti from porous and semi porous surfaces
- * Harmless to most plastics and metals. Test sensitive plastics on a small area first.
- * Low odour product
- * Effective and economical in use

TECHNICAL
DATA
SHEET



Copyright Electrolube 2003

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.



Graffiti Remover Gel – Page 2

TYPICAL PROPERTIES

Form	Gelled, colourless liquid
Flash Point	< 0°C
Odour	Characteristic

PACKAGING

400ml aerosol

ORDER CODE

GRG400

TECHNICAL DATA SHEET



Copyright Electrolube 2003

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

