

OP9020 Machine Cleaner & Resin Remover

Product Code: OP9020

PRODUCT DESCRIPTION

OP9020 is a special solvent designed to remove epoxy and polyurethane resin in the uncured state from machines and work surfaces.

OP9020 is a non-halogenated solvent offering lower toxicity than other halogenated solvents.

PRODUCT USE

The articles to be cleaned of uncured resin may include finished electronic components or production equipment such as tools, containers and jigs etc. Heavily soiled items should be soaked in **OP9020** and with a gentle rubbing action of a brush, pipe cleaner or rag the resin will dissolve and lift away. Lightly soiled items may only require a wipe with a damp rag containing **OP9020**.

Once the solvent has been used the container needs to be sealed to prevent evaporation and water absorption.

OP9020 will not generally attack metals but some plastic substrates may be attacked. It is always advisable to carry out test applications of **OP9020** cautiously to ensure that the article to be recovered is not itself damaged.

If the removal of cured product is required **OP9020** is not recommended; a more aggressive solvent such as **OP9003** or **OP9004** is required.

HEALTH & SAFETY NOTES

The main hazard associated with **OP9020** is that the material is **FLAMMABLE**. Please refer to the Material Safety Data Sheet for full information.

OP9020 is a volatile solvent and hence precautions are needed to prevent the build up of high concentrations of vapour.

TECHNICAL
DATA
SHEET

Copyright Electrolube 2003

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.



OP9020 Machine Cleaner & Resin Remover – Page 2

TECHNICAL
DATA
SHEET

Where anything but small amounts are being used then the work area must be well ventilated. Keep **OP9020** in closed sealed containers when not in use.

Threshold Limit Value:	100 ppm
Flash Point:	35°C
Density:	0.93 g/ml
Water Solubility:	Completely Soluble

High atmospheric concentrations can cause irritation to eyes, nose, throat and air passages.

Copyright Electrolube 2003

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

