

Surface Mount Rework Flux

Product Code: SMFL/SMF

PRODUCT DESCRIPTION

Electrolube Surface Mount Rework Flux is a quick drying, mildly activated (RMA type) no-clean flux in aerosol form for use when removing and replacing surface mount components. The aerosol is fitted with a wide angle actuator to give a protective film and an extension tube actuator for pinpoint application. Particularly recommended for precision products e.g. telecommunications or professional computers where a high degree of reliability is required.

PRODUCT USE

- * Application of spray flux to solder joints will aid reflow when heating to remove components.
- * After removing components excess solder should be removed from solder pads using **Electrolube Desolder Braid** aided by a squirt of spray flux.
- * **SMFL** should be applied to solder pads for placement of new components when using **Electrolube Surface Mount Solder Paste** with hot air or hot gas, or using conventional solder and iron.
- * Spray flux can also be used as an anti-tarnish, protective film on bare copper or tinned tracks providing excellent solderability for up to six months.

FEATURES


- * Available in CO₂ propelled aerosol and pen type dispensers.
- * 100% Ozone Friendly.
- * Zero halide content so no cleaning is required.
- * Passes copper plate and copper mirror corrosion (residue) test.
- * For use with hot air, hot gas or conventional soldering techniques.
- * Excellent solderability. Excellent solder spreadability.
- * Very high reliability.
- * Low non tacky/non corrosive residue.

TECHNICAL
DATA
SHEET



**Copyright
Electrolube
2003**

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.



Surface Mount Rework Flux – Page 2

TYPICAL PROPERTIES

Flux Type:	Mildly activated resin (RMA)
Colour:	Pale Straw
Drying Times:	5-10 minutes at room temperature
Halide Content:	0
Non-volatile Content:	18%
Flash point	12°C

PACKAGING

12ml Pen - Packed in 5's
200ml Aerosol (100% Ozone Friendly)

ORDER CODE

SMF12P
SMFL200D

TECHNICAL DATA SHEET



Copyright Electrolube 2003

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

