

## Screen & Stencil Solvent

Product Code: SSS

### PRODUCT DESCRIPTION

**Electrolube's Screen & Stencil Solvent** is an extremely effective cleaner which is classified as non-flammable. It exhibits excellent solder paste and adhesive removal. **SSS** is water rinseable and suitable for use in automated stencil cleaning equipment. **SSS** is available in bulk for use in automated systems and a 500ml trigger spray bottle for hand applications.

### PRODUCT USE

**SSS** is classified as non-flammable, hence flame proof equipment is not required. The solution is highly effective at ambient temperatures thus keeping running costs to a minimum.

**Electrolube's Screen & Stencil Solvent** is non foaming and surfactant free which means that there is minimal re-deposition of solder particles onto stencils and screens. **SSS** maintains a high load of excess paste in suspension to enable a good level of filtration. This results in clean stencils and screens without excess deposits of solder particles on the base of the cleaning equipment, reducing down time and cost.


A short cleaning cycle of three minutes for light deposits and five minutes for heavy, aged deposits makes this material suitable for a high speed production environment.

Heating is not normally required, although the **Screen & Stencil Solvent** may be heated to 35-40°C with the appropriate equipment. No extraction is required under normal conditions.

### FEATURES


- \* Solvent based
- \* Water rinseable
- \* Non flammable
- \* Biodegradable
- \* Excellent cleaning of pastes and adhesives
- \* Short cleaning cycle
- \* Heating not required
- \* Low odour

TECHNICAL  
DATA  
SHEET



**Copyright  
Electrolube  
2003**

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.



## Screen & Stencil Solvent – Page 2

\* Extraction not required under normal conditions

### TYPICAL PROPERTIES

Boiling Point	>100°C
Flash Point	61°C
Relative Density (20°C)	1.025
Form	Liquid
Colour	Colourless

### PACKAGING

5 Litre  
25 Litre  
500ml trigger spray

### ORDER CODE

SSS05L  
SSS25L  
SSS500ML

### TECHNICAL DATA SHEET



### Copyright Electrolube 2003

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

